

# ELEKTRODE DRYER TYP WED 5 / 350

## Technical Data

Capacity 25 kg

Input voltage  
230V

Power output  
0,9 kW

Temperature  
max 350°C

Dimensions H/W/D  
650 x 210 x 216

Weight 9kg

## Order number

225350

All technical specifications are target values.  
Dryfast GmbH & Co. KG reserves the right to change them without prior notice.  
No liability is accepted for damage resulting from use.



- **ROBUST CONSTRUCTION**
- **CAPACITY 25kg**
- **VARIABLE ADJUSTABLE 100°C – 350°C**
- **900 Watt HEATING POWER**
- **CENTRAL CHIMNEY**
- **HEAT BUFFER**

The Dryfast welding electrode dryer WED 5/350 is the ideal model for mobile as well as workshop applications in the field of re-drying.

Thanks to the infinitely variable thermostatic control, the WED 5/350 electrode dryer is extremely versatile.

The robust, double-walled and well-insulated housing is made of powder-coated and galvanised sheet steel.

The electrode dryer in the WED 1/350 series are equipped with a 230V connection cable with a Schuko plug.

The innovative design with the central-vertical radiator ensures good temperature distribution.

Ventilation of the moisture-saturated atmosphere is ensured via the exhaust air duct on the lid.

All these features make the WED 5/350 the ideal device for construction sites and stationary applications.

Dryfast GmbH & Co.KG  
Domänenstr. 38  
D-44225 Dortmund  
Phone +49 (0) 231 – 72 73 865  
Mail [info@dryfast.de](mailto:info@dryfast.de)  
Internet [www.dryfast.de](http://www.dryfast.de)